

# Fujitsu Siemens SCALEOVIEW L19-2 PC Monitor



Manufacturer's #: **S26361-K1117-V172**

## Description

- 19" (48cm) LCD Display
- Excellent [contrast](#) 700:1
- [Brightness](#) 300cd/m2
- Fast [response time](#) (typ.) 5ms
- Optimum flicker-free and distortion-free ergonomics
- Low price

Fujitsu Siemens SCALEOVIEW L19-2 - Flat panel display - TFT - 19" - 1280 x 1024 - 300 cd/m2 - 700:1 - 5 ms - 0.294 mm - [DVI](#) -D, [VGA](#) - speakers

## Specifications

### Overview

<b>Manufacturer's Part Number:</b>	S26361-K1117-V172
<b>Dot Pitch / Pixel Pitch:</b>	0.294 mm
<b>Image Contrast Ratio:</b>	700:1
<b>Image Brightness:</b>	300 cd/m2
<b>Manufacturer Warranty:</b>	3 years warranty
<b>Product Description:</b>	Fujitsu Siemens SCALEOVIEW L19-2 - flat panel display - TFT - 19"
<b>Colour:</b>	( the image of the product displayed may be of a different colour )
<b>Compliant Standards:</b>	Plug and Play, FCC Class B certified, CE, DDC-2B, EN 60950, EN 61000-3-2, EPA Energy Star, GS, ISO 13406-2, NEMKO, TCO '99, VESA FPMPI, EN 61000-3-3, EN50082-1, EN55022 Class B, FCC Part 15
<b>Colour support:</b>	Up to 16.2 million colors
<b>Device Type:</b>	Flat panel display / TFT active matrix

<b>Dimensions (WxDxH):</b>	41 cm x 21.4 cm x 37.5 cm
<b>Built-in Devices:</b>	Stereo speakers
<b>Weight:</b>	4.5 kg
<b>Power Consumption Operational:</b>	50 Watt
<b>Response Time:</b>	5 ms
<b>Power:</b>	AC 120/230 V ( 50/60 Hz )
<b>Audio Output:</b>	Speaker(s) - stereo - integrated
<b>Diagonal Size:</b>	19"
<b>Viewable Size:</b>	19"
<b>Max Resolution:</b>	1280 x 1024
<b>Digital Video Standard:</b>	Digital Visual Interface (DVI)
<b>Signal Input:</b>	DVI-D, VGA
<b>Display Positions Adjustments:</b>	Tilt

## General

<b>Display Type:</b>	Flat panel display / TFT active matrix
<b>Built-in Devices:</b>	Stereo speakers
<b>Width:</b>	41 cm
<b>Depth:</b>	21.4 cm
<b>Height:</b>	37.5 cm
<b>Weight:</b>	4.5 kg
<b>Enclosure Colour:</b>	( the image of the product displayed may be of a different colour )

## Manufacturer Warranty

<b>Service &amp; Support:</b>	3 years warranty
<b>Service &amp; Support Details:</b>	Limited warranty - 3 years - on-site

## Power

<b>Voltage Required:</b>	AC 120/230 V ( 50/60 Hz )
<b>Power Consumption Operational:</b>	50 Watt
<b>Power Consumption Stand by / Sleep:</b>	1 Watt

## Expansion / Connectivity

- |                    |   |   |
|--------------------|---|---|
| <b>Interfaces:</b> | • | 1 x <a href="#">VGA</a> - 15 pin HD D-Sub (HD-15)               |
|                    | • | 1 x <a href="#">DVI</a> -D - 24 pin digital <a href="#">DVI</a> |
|                    | • | 1 x audio line-in - mini-phone stereo 3.5 mm                    |

## Image

<b>Image Brightness:</b>	300 cd/m2
<b>Image Contrast Ratio:</b>	700:1
<b>Image Max H-View Angle:</b>	170
<b>Image Max V-View Angle:</b>	155

## Video Input

<b>Analogue video Signal:</b>	RGB
<b>Digital Video Standard:</b>	Digital Visual Interface (DVI)

## Miscellaneous

<b>Cables Included:</b>	<ul style="list-style-type: none"><li>• 1 x <a href="#">VGA</a> cable - 1.8 m</li><li>• 1 x audio cable - 1.8 m</li></ul>
<b>Flat Panel Mount Interface:</b>	100 x 100 mm
<b>MTBF:</b>	70,000 hour(s)
<b>Features:</b>	Security lock slot (cable lock sold separately)
<b>Compliant Standards:</b>	Plug and Play, FCC Class B certified, CE, DDC-2B, EN 60950, EN 61000-3-2, EPA Energy Star, GS, ISO 13406-2, NEMKO, TCO '99, VESA FPMPI, EN 61000-3-3, EN50082-1, EN55022 Class B, FCC Part 15

## Environmental Parameters

<b>Min Operating Temperature:</b>	5 °C
<b>Max Operating Temperature:</b>	35 °C

## Display

<b>Diagonal Size:</b>	19"
<b>Viewable Size:</b>	19"
<b>Dot Pitch / Pixel Pitch:</b>	0.294 mm

<b>Max Resolution:</b>	1280 x 1024
<b>Colour support:</b>	Up to 16.2 million colors
<b>Max Sync Rate (V x H):</b>	75 Hz x 81 kHz
<b>Response Time:</b>	5 ms
<b>Controls / Adjustments:</b>	Volume, brightness, contrast, H/V position, colour temperature
<b>Display Positions Adjustments:</b>	Tilt
<b>OSD Languages:</b>	English, German, French, Italian, Polish, Russian, Spanish, Dutch
<b>Backlight Life:</b>	50,000 hour(s)
<b>Signal Input:</b>	DVI-D, VGA

## Audio Output

<b>Type:</b>	Speaker(s) - stereo - integrated
<b>Output Power / Channel:</b>	1 Watt